## **EUROPEAN PATENT OFFICE**

## **Patent Abstracts of Japan**

08017179 **PUBLICATION NUMBER** 19-01-96 **PUBLICATION DATE** 

**APPLICATION DATE** 28-06-94 APPLICATION NUMBER 06146738


APPLICANT: YUASA CORP;

INVENTOR: KAGAWA HIROSHI;

: G11B 33/12 G11B 33/06 H01M 2/10 INT.CL.

**BATTERY INCORPORATED IN** TITLE

**ELECTRONIC EQUIPMENT** 



ABSTRACT: PURPOSE: To eliminate a battery holder, a battery contact piece etc. and to reduce the number of parts and man-hours by using a film battery as a battery incorporated in an electronic equipment and bringing the film battery in close contact to a printed circuit board in one piece.

> CONSTITUTION: A film battery 30 is a high-performance battery with a high energy density, a macromolecular solid electrolyte 33 is laid out between a positive electrode (manganese dioxide) 31 and a negative electrode (lithium, etc.) 32, the surrounding of pyroelectrics (also used as armored body) 34 and 35 of the positive and negative electrodes consisting of a metal plate (foil) is sealed by a sealing material 36. Then, with double-sided patterns 100 and 101 in a substrate 12, a conductor 42 is plate to a through hole 41 for continuity. Similarly, the area between the substrate 12 and the electrode of the film battery 30 continues via a through hole, thus efficiently incorporating a battery into a narrow space in an electronic equipment.

COPYRIGHT: (C)1996,JPO